



Compact Scanner for Multi-Operator 2G-5G Testing

Scanning Receiver | 10 MHz - 8 GHz | 24 - 48 GHz



The *Gflex*® scanning receiver is the next generation of mobile network testing from PCTEL®. Designed to support drive testing, walk testing, and government applications for 2G-5G and beyond, the *Gflex* sets a new standard for power, portability, and flexibility in a 5G and mmWave capable scanner. A single lightweight *Gflex* scanner can collect all the mmWave and sub-8 GHz data you need for drive test, walk test, and government applications in one pass, with one unit.

Technologies

- 5G NR
- LTE FDD
- TD-LTE
- LTE C-V2X
- NB-IoT
- UMTS
- GSM
- WiFi 6

Spectrum analysis and custom power measurements for any channel

Features

- Measures up to 120 5G channels
- Ultra-fast simultaneous 5G/4G/3G/2G testing
- I/Q streaming/capture
- 20/100 MHz wide step IF filter
- 5G/4G/3G/2G mobile blind scan
- Simultaneous NTN & terrestrial 4G/5G testing
- Dual polarization beamforming measurements
- 4G/5G Dynamic Spectrum Sharing (DSS)
- 4x2 and 2x2 LTE MIMO Measurements

Applications

- Optimization & troubleshooting
- Multi-network benchmarking
- NTN validation & compliance
- V2X network testing
- Spectrum clearing
- In-building wireless
- Signal intelligence
- Interference detection
- Coverage assurance



Gflex® Features & Benefits

FAST AND POWERFUL

Streamline your operations with a single-unit scanning receiver that does the work of multiple devices. One *Gflex* scanner has the power to test 120 5G channels simultaneously across mmWave and sub-8 GHz bands. With *Gflex*'s multi-core processing, you'll get ultra-fast scan speeds even when adding 4G measurements.

Test Up to 120
5G Channels
Simultaneously

PORTABLE & CONVENIENT

Save time and simplify setup with a single lightweight, compact scanner unit for complete 2G-5G indoor and outdoor testing on every operator network. The *Gflex* is easy to integrate into your test setup, with support from multiple software platforms. It even includes a hot-swappable battery pack for easy all-day walk testing.

Benchmark
Multi-Operator
2G-5G with
One Unit

FUTURE PROOF

Maximize your investment with a scanner designed for 5G and beyond. The expanded mmWave and sub-8 GHz range covers every 5G band¹. With a 20/100 MHz wide step IF filter, it's also the first purpose-built drive test/walk test scanner that measures the full 5G bandwidth.

Measure the
Full Channel on
Every 5G Band¹

FLEXIBLE

The field-upgradeable *Gflex* scanner adapts to your needs, including I/Q streaming and capture for government applications such as signal intelligence. It also supports simultaneous testing of terrestrial and Non-Terrestrial Networks (NTN), Cellular Vehicle-to-Everything (C-V2X), and a wide variety of 5G network configurations.

Support
Government
Applications with
I/Q Testing



Gflex® Specifications

5G New Radio (NR)

Measurement modes	NR TopN Signal: Synchronization channels (P-SS/S-SS) & PBCH; Layer 3 Reporting: MIB (FR1 and FR2), SIBs 1-9 (FR1); SIB1 (FR2 - nrTopN mode only); Dual polarization beamforming measurements; Blind Scan; Mobile Blind Scan	
Data modes	PCI, Beam Index, PSS-RP [dBm], SSS-RP [dBm], PSS-RQ [dB], SSS-RQ [dB], PSS-CINR [dB], SSS-CINR [dB], RSPBCH-RP [dBm], RSPBCH-RQ [dB], RSPBCH-CINR [dB], SSB-RP [dBm], SSB-RQ [dB], SSB-CINR [dB], SSB-idx, SSB-RSSI, SSS-Delay-Spread, Time Offset	
Sub carrier spacing	15/30/120/240 kHz	
Max. number of channels	60 (sub-8 GHz), 60 (mmWave)	
Max. number of PCIs	16 (sub-8 GHz), 16 (mmWave)	
Max. number of beams/PCI	8 (sub-8 GHz), 64 (mmWave)	
Measurement rate (typical)	Single channel: FR1: 44/sec (20 ms period) FR2: 44/sec (20 ms period)	Multi-channel: FR1: 33/sec sub-8 GHz (20 ms period) FR2: 25/sec mmWave (20 ms period)
Dynamic range (CINR)	PSS/SSS CINR: -21 to +33 dB (sub-8 GHz), -21 to +28 dB (mmWave) PBCH DMRS CINR: -16 to +40 dB	
Min. detection level	RP	SCS @15 kHz: -135 dBm, SCS @30 kHz: -132 dBm, SCS @120 kHz: -131 dBm, SCS @240 kHz: -130 dBm
Accuracy (CINR)	PSS/SSS, PBCH DMRS	±2 dB
SSB periodicities supported	5 ms, 10 ms, 20 ms, 40 ms, 80 ms, 160 ms	

LTE FDD and TD-LTE

Measurement modes	Top N Synchronization Channel Reference Signal (P-SCH/S-SCH) and Resource Block (Wideband, Subband), Dynamic Spectrum Sharing (DSS), Layer 3 Reporting, Blind Scan, Mobile Blind Scan, Non-Terrestrial Networks (NTN)		
Data modes	PCI, RP, RQ, CINR, Cyclic Prefix, Time Offsets, Delay Spread; RF Path Measurements (4x1, 4x2); MIMO: Condition Number, ECQI, EPUT; NTN: Frequency Offset		
Channel bandwidths	1.4 / 3 / 5 / 10 / 15 / 20 MHz		
Max. number of channels	48		
Receive modes	SISO; MIMO (2x2, 4x2)		
Transmit antenna configurations	1, 2, 4 (with path measurement)		
Measurement rates (LTE Ultra High Speed mode)	Sync Channel RS	Single channel: LTE FDD: 175/sec TD-LTE: 90/sec	Multi-channel: LTE FDD: 150/sec TD-LTE: 75/sec
Dynamic range (CINR) @ 10/15/20 MHz	RS P-SCH/S-SCH	-26 to +40 dB -10 to +18 dB	
Min. detection level	P-SCH/S-SCH & RS	-147 dBm (RSRP @ 15 kHz)	
Accuracy (CINR)	P-SCH/S-SCH & RS	±1 dB	
Max. number of PCIs	24		

LTE C-V2X

Measurement modes	PSCCH, PSSCH		
Data modes	RSRP, RSSI, CINR, Direct Frame Number, Direct Sub Frame Number, Subchannel, Channel Busy Ratio		
Transmission mode	TM4		
Min. detection level	PSCCH	-140 dBm	
Dynamic range (CINR)	PSCCH	-7 dB to +34 dB	
Measurement rate	PSCCH	9 /sec (if Resource Pool parameters are available); PSCCH Auto Detect scan for detecting Resource Pool is available but has a slower measurement rate	

NB-IoT (LTE)

Measurement modes	Top N NRS (Narrowband Reference Signal), NPSS (Narrowband Primary Synchronization Signal), and NSSS (Narrowband Secondary Synchronization Signal), Layer 3 Reporting, Blind Scan, Mobile Blind Scan		
Data modes	NRS: RP, RQ, RSSI, CINR, Time Offset; NPSS: RP, RQ, RSSI, CINR; NSSS: RP, RQ, RSSI, CINR, Time Offset		
Operation mode	In-Band, Guard Band, Stand-alone (eTopN mode only)		
Channel bandwidths	180 kHz		
Max. number of channels	48		
Measurement rates	5/sec		
Dynamic range (CINR)	NRS	-15 to +40 dB	
Min. detection level	NRS RP	-138 dBm	
Accuracy (CINR)	NRS	±2 dB	
Max. number of PCIs	16		

UMTS [WCDMA/HSPA(+)]

Measurement modes	Top N Pilot, Layer 3 Reporting, Blind Scan, Mobile Blind Scan		
Data modes	I _o , Ec/I _o , Aggregate Ec/I _o , SIR, Rake Finger Count, Time Offset, Delay Spread		
Channel bandwidths	200 kHz / 3.84 MHz		
Max. number of channels	32		
Measurement rate	50/sec (high dynamic range mode only)		
Top N CPICH dynamic range (Ec/I _o)	-26 dB		
Min. detection level	-127 dBm		
Accuracy	±1 dB		
Max. number of Pilots	32		

GSM

Measurement modes	Color Code, Layer 3 Reporting, Blind Scan, Mobile Blind Scan		
Data modes	BSIC, C/I, RSSI		
Channel bandwidths	30 kHz / 200 kHz		
Measurement rates	Up to 400 BSIC Decodes/sec		
Dynamic range	+2 dB C/I		
Min. basic detection level	-110 dBm		
Accuracy	±1 dB		

GPS

Type	72 channel internal receiver		
Position accuracy	2.5 meters		
Acquisition time	Cold start: <26 sec; Hot start: <2 sec		
Sensitivity (tracking)	>-150 dBm		

WiFi 6

Wireless adapter	D-Link AX1800 Wi-Fi 6 USB Adapter DWA-X1850, ASUS Wi-Fi 6 AX1800 USB Wi-Fi Adapter		
Radio configuration	802.11 a/n/ac/ax		
Data modes	Signal Strength, Channel Number, Channel Bandwidth, BSSID, Device Name, SSID, Security Protocol, 802.11 Media, Beacon Interval, Channel Utilization		
Frequency range	2.4 – 2.483 GHz; 5.15 – 5.85 GHz (subject to country regulations)		
Measurement rates	2-3 sec/measurement (typical)		

VITA 49.2 I/Q Streaming/Capture

Frequency ranges	10-8000 MHz, 24-48 GHz
Instantaneous BW	20 MHz, 50 MHz, 100 MHz
Channel sampling rate	30.72 Msps, 61.44 Msps, 122.88 Msps
I/Q Data Format	16 bit I, 16 bit Q
Communication interfaces	10-GigE SFP+ (Continuous I/Q streaming @ 20 or 100 MHz) for 10-8000 MHz, 24-48 GHz 10/100/1000 Ethernet RJ-45 (I/Q capture - 2 seconds maximum @ 20 MHz) for 10-8000 MHz
Communication protocol	UDP
Maximum data rate	5 Gbps for 10-GigE SFP+ @ 20 or 100 MHz for 10-8000 MHz, 24-48 GHz 1 Gbps for 10/100/1000 Ethernet RJ-45 @ 20 MHz for 10-8000 MHz
Time base/ frequency accuracy	GPS disciplined; When lost, OCXO has a frequency stability of 5 ppb
NF at minimum attenuation	7 dB for $f < 8$ GHz, 12 dB for $24 \text{ GHz} < f < 48$ GHz
Attenuator range/step	7 attenuation indices from 0 dB to 30 dB in steps of 5 dB

GPS/GNSS

Supported navigation systems	Galileo, GPS, GLONASS, BeiDou, QZSS
Type	72 channel internal receiver
Position accuracy	2.5 meters
Acquisition time	Cold start: <26 sec; Hot start: <2 sec
Sensitivity (tracking)	>-150 dBm

Power Measurements

Accuracy	±1 dB (across basic RF input power range)	
Dynamic range	-120 to -20 dBm @ 30 kHz	
RSSI	5G NR, LTE UMTS	11,050 ch/sec (maximum, contiguous channels) 4,250 ch/sec (maximum, contiguous channels)
Enhanced Power Scan (EPS)	5 kHz to 20 MHz in 2.5 kHz increments	1,000 MHz/sec @ 5 MHz (typical)
Spectrum analysis	Range: >90 dB	>270 MHz/sec (single sweep)

Physical

Maximum power (+9 to +17 VDC)	40W max.
Size	6.42" W x 8.13" D x 2.37" H (163 mm W x 207 mm D x 60 mm H)
Weight	4.8 lbs (2.18 kg)
Temperature range	Operating: 0°C to +50°C; Storage: -30°C to +80°C
Humidity	5% to 95% relative humidity, non-condensing
Host data communications interface	USB 3.0, 10/100/1000 Ethernet RJ-45, 10-GigE SFP+, Bluetooth®
Antenna ports	RF (sub 8 GHz, Bluetooth): SMA Female (50 Ω); GPS: Male (50 Ω) SMB; RF (mmWave): 2.4 mm Female
Safety	EN 62368-1
EMC	EU 2014/53/EU
Shock and vibration	SAE J1455
RoHS	Directive 2011/65/EU and amendment 2015/863 (RoHS 3)

RF Characteristics

Frequency ranges	Sub 8 GHz: 10 MHz – 8 GHz mmWave: 24.25-44 GHz (continuous), 47.2-48.2 GHz (continuous)
Internally generated spurious response	-105 dBm (typical)
RF operating range	In-Band -20 dBm max.
Desensitization	Adjacent channel >50 dB (20MHz RBW)
Safe RF input range	≤ +0 dBm
Frequency accuracy	±0.05 ppm (GPS Locked); ± 0.1 ppm (GPS unlocked)
Conducted local oscillator	-55 dBm (typical)
Intermodulation-free dynamic range	2 tone @ -25 dBm, 8 GHz, +10 dBm typical TOI; @ -40 dBm, 8 GHz, -10 dBm typical TOI; @ -25 dBm, 24.25-40 GHz, -3 dBm typical TOI; @ -40 dBm, 24.25-40 GHz, -10 dBm typical TOI; @ -40 dBm, 40-44 GHz, 47.2-48.2 GHz, -12 dBm typical TOI

Supported bands, technologies, data modes, software features, and frequency ranges vary by scanning receiver configuration. Upgrades may be available for previously purchased scanning receivers. Please contact a sales representative for more information.



PCTEL, Inc.

T: +1 301 515 0036 | pctel.com

¹As of 3GPP Release 17 V17.2.0 (2021-06)
Specifications subject to change without notice. PCTEL® and Gflex® are registered trademarks of PCTEL, Inc. Bluetooth® is a registered trademark of Bluetooth SIG. ©2025 PCTEL, Inc.
All rights reserved. Rev. P (November 2025)